



**3 Type**

- C** Angled lever with plain bore H7
- E** Angled lever with threaded bore
- B** Straight lever with plain bore H7
- D** Straight lever with threaded bore

1 2 2

**Steel**

d <sub>1</sub>	d <sub>2</sub> Thread		d <sub>3</sub> H7 Bore		d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub> ≈	l <sub>1</sub> ≈		l <sub>2</sub> ≈	t <sub>1</sub> min.	t <sub>2</sub> min.	
	Type E	Type D	Type C	Type B					Type C Type E	Type B Type D				
22	M 10	M 10	B 10	B 10	8	20	37	67	40,5	89,5	96	85	15	19
25	M 12	M 12	B 12	B 12	10	25	42	76	47	100,5	107,5	95	18	21
28	M 12	M 12	B 12	B 12	12	30	47	87	53	114	122	108	18	23
32	M 16	M 16*	B 16	B 16*	12	32	52	98	59	133	142	126	23	28
36	M 16	M 16	B 16	B 16*	14	35	58	108	64,5	146	156	138	24	28
40	M 20	M 20*	B 20	B 20	16	40	64	120	72	162,5	174	154	27	30

1 2

\* not available from stock, requires a minimum order quantity

**Stainless steel**

d <sub>1</sub>	d <sub>2</sub> only type E	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub> ≈	l <sub>1</sub> ≈	l <sub>2</sub> ≈	t <sub>1</sub> min.
22	M 8	8	20	37	67	89,5	85	18
25	M 10	10	25	42	76	100,5	95	18
28	M 12	12	30	47	87	114	108	20
32	M 16	12	32	52	98	133	126	25

**Specification**

- Steel —
- Blackened —
- Stainless steel AISI 303 **NI**
- Matte shot-blasted
- Ball knobs DIN 319 Plastic, Duroplast Black, shiny finish
- Cross Holes GN 110 → Page 2080
- ISO Fundamental Tolerances → Page 2151
- Stainless Steel Characteristics → Page 2166
- RoHS

4

**Information**

Tension levers GN 212 are used as clamping element as well as operating levers.

see also...

- Adjustable Tension Levers GN 212.3 (Steel, Blackened) → Page 480
- Adjustable Stainless Steel Tension Levers GN 212.5 → Page 482

**How to order (Steel)**

**GN 212 -28-B12-C**

1	d <sub>1</sub>
2	d <sub>3</sub> (d <sub>2</sub> )
3	Type

**How to order (Stainless steel)**

**GN 212-25-M10-E-NI**

1	d <sub>1</sub>
2	d <sub>2</sub>
3	Type
4	Material